


Venn 500 TCD UL

Road disc brake carbon rim, 50 mm deep, 1k filament wound. 5-year rim warranty.



Section at 2:1 when printed at 100% on A4. Figures in mm.

ERD	540.5 mm Factory figure
Internal width	25 mm
External width	32 mm widest; 29.5 mm at the bead
Depth	50 mm
Weight	345 ± 15 g Raw finished rim, no clear coat
Wheel size	700c / 29" (ISO 622)
Spoke holes	24 or 28 Drilled after moulding
Maximum spoke tension	130 kgf
Brake	Disc
Tyre	Tubeless ready, hooked Tubeless or with inner tubes
Rider weight limit	110 kg

FOR THE BUILD

- **Spoke length.** Use the ERD above. Before cutting spokes for a full order, measure one rim from the batch.
- **Nipples.** Order with tool access holes for internal nipples (the rim then needs tubeless tape), or without them for a true tubeless rim bed (external nipples only).
- **Finish.** Gloss uncoated, matte uncoated or filament wound 25k (+25 g per rim). Decals: black or none.

TESTED

- **Impact:** 100 J pass mark for road disc brake rims. The UCI's wheel requirement is 40 J (ISO 4210-7). A pass mark is the energy every rim must pass, not a failure point.
- **Spoke holes:** pull-through tested; pass mark 300 kgf.
- Every rim model goes through the same programme: fatigue, run-out, spoke hole strength, lateral rigidity, tyre retention and heat.